

imagePROGRAF & imagePROGRAF® iPF755/750






TECHNICAL DOCUMENTS

LARGE-FORMAT PRINTING

image**PROGRAF**



SPECIFICATIONS

Print-Head

PF-04

Technology FINE (Full-Photolithography Inkjet Nozzle Engineering)

Print Resolution (Max.)

2400 × 1200 dpi

Line Accuracy*

±0.1% or Less

Minimum Line Weight**

0.02mm

Number of Nozzles

Matte Black: 5.120 Nozzles

Other Colors: 2,560 Nozzles per Color

Droplet Size

4 Picoliter

Nozzle Pitch (Head Resolution)

1200 dpi × Two Rows

Print-Head Swath 1.07 inch

Ink Type

Dye

Cyan (C), Magenta (M), Yellow (Y), Black (K)

Pigment

Matte Black (MBK)

Ink Tank

PFI-102: MBK, C, Y, K

PFI-104: M
Ink Tank Capacity

Starter: 90ml Replacement: 130ml

Ink Supply Method

Tubing System with Sub-Tanks for Continuous

Ink Supply

Nozzle Recovery System

Non-firing Nozzle Detection and Compensation

Printer Controller

L-COA Controller

Printer Memory

256MB Hard Drive (iPF755 only)

80GB (SATA)

Mail Boxes (User Job Storage) (iPF755 only)

1 Common Inbox, 29 User Inboxes

(Password-protected)

Media Feed Roll Feed

One Roll, Top-loading, Front Output

Cut Sheet

One Sheet, Top-loading, Front Output

Media Width

Roll Feed 10" – 36" (254mm – 914mm)

Cut Sheet

8" – 36" (203.2mm – 914mm)

Printable Margins

Roll Feed

All Sides: 0.12" (3mm) or 0" for Borderless

Cut Sheet

Leading, Sides (Left and Right): 0.12" (3mm) Trailing: 0.91" (23mm)

Maximum Print Length (Single Page)†

Roll Feed 59' (18m)

Cut Sheet

Borderless Printing Widths (Roll Media Only) 10", B4, A3, 14", A2, 17", B2, A1, 24", B1, A0, 36"

Specifications and availability subject to change without notice.

Media Cutter

Durable Dual-blade Rotary Cutter

Media Thickness 0.07 – 0.8mm (2.8 – 31.4mil)

Media Core Sizes

2" and 3" Core (Adapter Included)
Maximum Roll Outer Diameter

5.9" (150mm)

Output Media Bin

Stackable Media Basket (Standard)

Output Media Bin Capacity
20 Sheets (With Stackable Configuration)

Printing Software

ting Sonware
imagePROGRAF Printer Driver for Windows/Mac,
HDI Driver¹¹, Printer Driver Extra Kit for Windows/
Mac (Free Layout, Color imageRUNNER®
Enlargement Copy, Advanced Preview), Print Plug-in for Microsoft Word/Excel/PowerPoint for Windows, Digital Photo Front-Access for Windows, PosterArtist Lite for Windows

Operating System[†]

Windows 32-bit 2000/XP/ Server 2003/ Windows Vista®/Server 2008, Windows 64-bit XP/ Server 2003/Windows Vista/Server 2008 Macintosh OS X CUPS (10.4.9, 10.5.x) 32-bit, Macintosh OS X CUPS (10.5.x) 64-bit (Available in

download only) Print Language

GARO, HP-GL/2, HP RTL

Interface
USB 2.0 Hi-Speed, 10/100/1000Base-T/TX

Protocol

TCP/IP (IPv4/IPv6), IPX/SPX, AppleTalk®, SNMP

(Canon MIB supported), HTTP

Acoustic Noise

Operation

50dB (A) or Less

Standby 35dB (A) or Less

Acoustic Power

Approx. 6.6 Bels

Power Supply AC 100–240V (50-60Hz)

Power Consumption

Maximum

140W or Less

Standby 5W or Less

Power Off

1W or Less (Executive Order Compliant)

Certifications

Electrical Safety Regulations

UL® (USA), C-UL (Canada), S mark (Argentina), CE mark (EN60950, EN55022 classB, EN61000-3-2, EN-61000-3-3, EN55024) (EU), CB certification (Others)

Electromagnetic Interface Regulations

FCC Class B (USA), IC Class B (Canada)

Environmental Certifications

ENERGY STAR® (Worldwide), RoHS Directive, WEEE, Executive Order (USA)

Operational Environment

Temperature

59 – 86 F° (15 – 30 C°) **Relative Humidity** 10 – 80% (No Condensation)

Printer Dimensions (H × W × D) and Weight with Stand and Basket

 $41.8" \times 51.3" \times 34.3"$

 $(1,062mm \times 1,304mm \times 870mm)$ Approx. 139 lb. (63kg)

Package Dimensions (H × W × D) and Weight+

7/70mm × 1,434mm × 830mm)
Approx. 166 lb. (75kg)

Stand Package 9.4" × 55.1" × 30.7" (1,585mm x 1,263mm × 2,348mm) Approx. 38 lb. (17kg)

Options

PosterArtist

Roll Holder Set (RH2-33)

User-Replaceable Items
Ink Tank (PFI -102 MBK, C, Y, K; PFI-104 M) Print-Head (PF-04)

Maintenance Cartridge (MC -10)

What's In The Box

Printer, User Software CD for Windows, User Software CD for Macintosh, User Manual CD, PosterArtist Lite CD, 6 Starter Ink Tanks (MBK×2, PosterArtust Lite CD, 6 Staffer Int anks (MBX.2, C, M, Y, K), 2" Core Media Spool with 3" Adapter, Print-Head PF.04, Maintenance Cartridge MC-10, Quick Setup Guide (Poster), Printer Reference Guide (Booklet), Power Cord, One-Year Onsite Limited Warranty, Registration Card, Stand, Stackable Media Basket, Accessory Box, Hardware (For Setting Up the Printer and Stand)

- * Line accuracy repeatability is guaranteed after a user performs necessary adjustment and under the same environmental conditions. Applies to media for line drawing (Plain Paper, Coated Paper, CAD Translucent Matte Film, and CAD Tracing Paper) only.
- Theoretical value based on data resolution.
- The maximum printable length varies, depending on the application, OS, and RIP used.
- †† For AutoCAD or AutoCAD LT 2000/2000i/2002/2004/ 2005/2006/2007/2008/2009
- For imagePROGRAF Printer Driver. For printing from PostScript® applications such as Adobe Illustrator® or QuarkXPress[™], please use a PostScript compatible RIP package. For a list of Canon recommended RIP packages, please consult with Canon Alliance and Industry Market program list of RIP vendors at www.usa.canon.com.
- The printer will be shipped on a pallet with stand box strapped on top of the main unit. Shipping dimensions and weight for iPF755/iPF750 are (H×W×D) 39.7" × 56.5" × 32.7", 205 lb.



1-800-OK-CANON www.usa.canon.com

Canon U.S.A., Inc. One Canon Plaza Lake Success, NY 11042

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. PostScript and Illustrator are registered trademarks of Adobe Systems Incorporated in the United States and/or other countries. AutoCAD is a trademark of Autodesk, Inc. in the United States. Macintosh and AppleTalk are registered trademarks of Apple Inc. Microsoft, Windows, and Windows Vista are registered trademarks of Microsoft Corporation in the United States and/or other countries. UL is a registered trademark of Underwriters Laboratories Inc. QuarkXPress is a trademark of Quark, Inc. and all applicable affiliated companies, Reg. U.S. Pat. and Tm. Off. and in many other countries. CANON, IMAGEPROGRAF, IMAGERUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All referenced product names and other marks are trademarks of their respective owners.







