

MODELS

V710 CRT Monitor
187895-001

Note: AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability.

SPECIFICATIONS

Picture Tube (diagonal)	17-in High-contrast Flat Faceplate CRT			
Viewable (diagonal)	16 in			
Horizontal Dot Pitch	0.20 - 0.25 mm			
Trio Dot Pitch	0.25 - 0.28 mm			
Max Refresh/Preset Graphic Modes	1600 x 1200	1280 x 1024		
	67 Hz/65 Hz	80/75 Hz		
	1024 x 768	800 x 600	720 x 400	640 x 480
	105 Hz/ 60, 75, 85 Hz	130 Hz/85 Hz	160 Hz/70 Hz	160 Hz/60 Hz

Note: All modes are non-interlaced unless specified otherwise.

Text Mode	720 x 400
	70 Hz

User-Programmable/Preset Graphic Modes	8/8
--	-----

Anti-Glare/Anti-Static	Yes/Yes
------------------------	---------

Plug and Play	Yes
---------------	-----

Approvals/Certifications	UL Approval	Yes
	ISO9241-3 VOT Guidelines Approval	Yes
	MPR-II Compliant	Yes
	FCC Approval	Yes
	Energy Star Compliant	Yes
	TCO 99 Compliant	Yes
	CE Marking	Yes
	GS Marking	Yes

On-Screen Controls	Yes
--------------------	-----

Language Selection	German	Yes
	English	Yes
	Spanish	Yes
	Italian	Yes
	Swedish	Yes
	Portuguese	Yes
	French	Yes
	Russian	Yes
Korean	Yes	

SPECIFICATIONS *(continued)*

Tilt Base (up/down)	13° up/5° down	
Swivel	± 45° left/right	
User Controls	Brightness, Contrast	Yes
	Size and Positioning	Yes
	Pincushion (barrel)	Yes
	Trapezoid	Yes
	Tilt (rotation)	Yes
	Color temperature	Yes
	Parallelogram	Yes
	Pincushion Balance	Yes
	Individual color control	Yes
	Moiré Cancellation	Yes
	Convergence	No
	Serial Number Display	Yes
	Degauss	Yes
	Factory Reset	Yes
AssetControl	Yes	

Note: When used with Compaq Intelligent Manageability CPUs and appropriate network software.

USB Capabilities	Option
Pixel Clock Speed	175.5 MHz
Input Impedance	75 ohms
Horizontal Frequency	30 to 85 kHz
Vertical Frequency	50 to 160 Hz
Power Supply	120 to 220 VAC
Maximum Power Rating	100 Watts
Power Consumption	15W/3W
Synch Input	TTL separate synch
Signal Cable	Captive 15-pin D-sub video cable
Dimensions (HxWxD)	16.34 in x 16.22 in x 16.63 in/415 mm x 412 mm x 422.5 mm
Weight	16.2 kg
Operating Temperature	50° to 95° F/10° to 35° C
Operating Humidity (non-condensing)	20% to 80%

48 Hour Direct Replacement	If this monitor fails during the parts warranty, Compaq guarantees that a new, or like-new monitor replacement will be delivered within 48 hours. <i>Note: Certain restrictions and exclusions apply. Consult the Compaq Customer Service Support Center for details.</i>
-----------------------------------	--

Limited Warranty	Three-year parts, labor and on-site <i>Note: Certain restrictions and exclusions apply. Consult the Compaq Customer Service Support Center for details.</i>
-------------------------	--

COMPATIBILITY

Portables

Compaq Armada 7800
Compaq Armada 7400
Compaq Armada 6500
Compaq Armada 3500
Compaq Armada 1750
Compaq Armada 1700
Compaq Armada 1500c

Desktops

Compaq Deskpro EN Series Desktop
Compaq Deskpro EN Series Minitower
Compaq Deskpro EN Series Small Form Factor
Compaq Deskpro EP Series

Workstations

Compaq Professional Workstation XP1000
Compaq Professional Workstation AP500

Servers

Compaq ProLiant 7000 Xeon™
Compaq ProLiant 6500 Xeon
Compaq ProLiant 6000 Xeon
Compaq ProLiant 5500 Xeon
Compaq ProLiant 3000 Pentium® III
Compaq ProLiant 3000 6/450
Compaq ProLiant 1600 6/500
Compaq ProLiant 1600 (100 MHz)
Compaq ProLiant 800 (500 MHz)

SMB

Compaq Prosignia Notebook Family of Personal Computers
Compaq Prosignia Desktop Family of Personal Computers
Compaq Prosignia 740
Compaq Prosignia 720

Compaq registered United States Patent and Trademark Office.
Other product names mentioned herein may be trademarks and/or registered trademarks of their respective companies.

©2001 Compaq Computer Corporation