

# Phaser® 3635MFP

## Black-and-White Multifunction Printer



	Phaser 3635MFP/S	Phaser 3635MFP/X
<b>Speed</b>	Up to 35 ppm letter / 33 ppm A4	
<b>Duty Cycle</b>	Up to 75,000 pages / month	
<b>Paper Handling</b>	Standard	<b>Duplex Automatic Document Feeder:</b> 50 sheets; Size: 5.5 x 8.5 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm; Weight: 12 to 28 lb / 50 to 120 gsm <b>Bypass Tray:</b> 50 sheets; Size: 3.9 x 5.8 in. to 8.5 x 14 in. / 98 x 148 mm to 216 x 356 mm; Weight: 16 to 43 lb / 60 to 163 gsm <b>Tray 1:</b> 500 sheets; Size: 5.85 x 8.27 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm; Weight: 16 to 28 lb / 60 to 105 gsm; Standard selectable sizes up to 8.5 x 14 / A4
	Optional	<b>Tray 2:</b> 500 sheets
Output	250 sheets, automatic two-sided	
Finishing	NA	<b>Offline Convenience Stapler:</b> 20-sheet, single position
<b>Print</b>	As fast as 9 seconds	
First-page-out-time	As fast as 9 seconds	
Print resolution	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)	
Memory (standard / max)	256 MB / 512 MB plus 80 GB Hard Drive	
Processor	360 MHz	
Language support	PostScript® 3™ compatibility, PCL® 6 and 5e emulations	
Connectivity	10/100 BaseT Ethernet, USB 2.0	
Print features	Custom page size, Automatic two-sided, Watermark, Secure print, Sample set, Delayed print, Cover selection, Paper selection by attribute, Toner saver, N-Up, Mirror image, Negative image, Image rotation, Saved settings, Booklet creation, Fit to new paper size, Collation, Print to Hard Drive, Print from Hard Drive, Print from USB memory drive	
<b>Copy</b>	As fast as 9 seconds	
First-page-out time	As fast as 9 seconds	
Copy resolution	600 x 600 dpi	
Copy features	Automatic two-sided, Collation, Reduce/Enlarge 25 to 400% from platen and ADF, Book copying, Mixed-size originals, Edge erase, Image shift, Booklet creation, Covers, Auto paper select, Lighten/darken, Transparency Separators, Multi-Up, ID Card Copy, Copy to Hard Drive, Background suppression	
<b>Fax</b>	NA	Embedded Fax (33.6 Kbps with MH, MR, MMR, JPEG and JBIG compression), LAN Fax
Fax features	NA	Up to 600 x 600 dpi (superfine) resolution, Color Fax send, Address Book, Priority send, Fax reports, Junk fax list, Junk fax prevention, Background suppression, Mailboxes, Polling, Forward to Fax / Email, Secure Fax, Fax broadcast
<b>Scan</b>	Scan to Email, Network Scanning, Scan to USB memory drive	
Scan destinations	Scan to Email, Network Scanning, Scan to USB memory drive	
Scan features	Up to 600 x 600 dpi; File formats: PDF, JPEG, TIFF, Multi-page TIFF; Xerox Scan to PC Desktop® Personal Edition (Includes 1 seat of OmniPage®, PaperPort®, and Image Retriever for use with network scanning), Color Scanning, FTP, HTTP, HTTPS, SMB	
<b>Accounting</b>	Xerox Standard Accounting (tracks copy, print, scan, fax), Network Accounting enablement supports optional Xerox Alliance Partner Solutions	
<b>Security</b>	Image Overwrite Security, SSL, Authentication, 802.1x, SNMPv3, IP Filtering, Audit Log, HTTPS, Secure Print, Secure Fax	
<b>Options</b>	Foreign Device Interface, 256 MB Memory Upgrade, Cabinet Stand, Network Accounting Enablement, Network Fax Server Enablement	
<b>Warranty</b>	One Year On-Site Warranty, Xerox Total Satisfaction Guarantee	

### Device Management

CentreWare® Internet Services, CentreWare Web, CentreWare for HP OpenView, CentreWare for IBM Tivoli NetView, CentreWare for Unicenter, CentreWare® Management Pack for Microsoft System Center Operations Manager (SCOM), Xerox Novell Distributed Print Services Solution (NDPS)

### Print Drivers

Windows 2000/2003 Server/XP/XP Professional/Vista, Macintosh OS X v10.3, Solaris 9/10, Red Hat ES, Linux, Fedora Core 4, SUSE, AIX 5, HP-UX 11.0/11i

### Media Handling

Media Types: Plain paper, recycled, bond, lightweight, heavyweight, envelopes, labels, transparencies, punched, letterhead, pre-printed, archive

### Operating Environment

Temperature: Maximum Range: 50°–90°F / 10°–32°C, Recommended Range: 61°–86°F / 16°–30°C



Humidity: Maximum Range: 20–80%, Recommended Range: 30–70%  
Electrical: Power: 110–127 VAC and 220–240 VAC, 50/60 Hz, Power Consumption: Average: 600 watts, Standby: 55 W, Power Saver mode: 15 W, ENERGY STAR® Qualified

### Dimensions (WxDxH)

18.6 x 18.8 x 21.4 in. / 472 x 478 x 543 mm  
Weight: 48.6 lbs. / 22.1 kg

### Agency Approvals

Listed to UL 60950-1/CSA 22.2 No. 60950-1-03, Class 1 Laser Product, FCC Part 15, Class A, CE marked in accordance with Low Voltage Directive, 2006/95/EC and EMC Directive 2004/108/EC, CB Certified against IEC 60950, Section 508 ADA

### What's in the box

- Phaser 3635MFP Multifunction Printer
- Print Cartridge (5,000 print capacity)
- World Kit (includes Printer Installer and utilities CD, Software and documentation CD, Registration card, Warranty booklet)
- Power cord

### Supplies and Options

High Capacity Print Cartridge – approx. 10,000*	108R00795
Standard Print Cartridge – approx. 5,000 pages**	108R00793
Network Accounting Enablement	098S04928
Network Fax Server Enablement	098S04931
256 MB Memory Upgrade	098N02189
Paper Tray	098N02190
Stand	097N01674
Foreign Device Interface Kit	097N01676
Staple Cartridge	108R00823

\*Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and media used.

\*\*Yield will vary depending on job run length, media size and orientation

