

The compact automatic double-sided laser printer for personal use.

i-SENSYS
LBP6200d

you can



Compact, desktop mono laser printer with automatic double-sided printing .

With automatic double-sided printing, this compact laser printer is a great addition to the home or small office. Benefit from maintenance free prints and a host of energy and time-saving features.

25 PPM
6 SECONDS FIRST
PRINT OUT TIME

SPACE-SAVING
DESIGN

DOUBLE-SIDED
PRINTING

ENERGY EFFICIENT

QUIET OPERATION

Key features

- Compact and stylish design
- Productive 25 ppm mono laser printing
- Automatic double-sided printing for reduced paper wastage
- First Print Out Time of only 6 seconds or less
- Up to 2400 x 600 dpi resolution with Automatic Image Refinement
- Efficient 1.4 W power consumption in sleep mode
- Quiet operation and inaudible in Standby mode
- Convenient, easy to use All-in-One cartridge

What's in the Box

Main unit, Cartridge 726 starter, power cord, setup sheet and warranty card - with user software CDs.

Dimensions (WxDxH)

379mm x 293mm x 243mm

Supported OS

Win 7(32/64bit) / Win Vista(32/64bit) / XP(32/64bit) / Server 2008(32/64bit) / Server 2008 R2(64bit) / Server 2003 (32/64bit) / 2000

Mac 10.4.9 - 10.6.X
(Web distribution only)

Linux (Web distribution only)



PRINT



COPY



FAX



SCAN

Canon



- 1 250-sheet multi-purpose tray
- 2 Cartridge 726

| | | | |
|---|--|---|--|
| PRINTER ENGINE Print speed Printing method Print quality Print resolution Warm-up time First Page Out Time Duty cycle Print margins | 25 ppm mono (A4) Monochrome laser beam printing Up to 2400 x 600 dpi with Automatic Image Refinement Up to 600 x 600 dpi Approx 0.5 seconds from Sleep Approx. 10 seconds or less from power on Approx. 6 seconds or less Max. 8,000 pages per month 5mm top, bottom, left and right | GENERAL FEATURES Power requirements Power consumption Noise level | AC 220-240V ($\pm 10\%$), 50/60Hz ($\pm 2\text{Hz}$) Maximum: Approx 1200W or less Active: Average approx 280W or less Standby: Average approx. 1.6W Sleep: Average approx 1.4W Typical Electricity Consumption (TEC): 0.7 kWh/week Sound power ¹ : Active: 6.77 B or less Standby: Inaudible |
| MEDIA HANDLING Paper input (Standard) Paper output Media types Media sizes | 250-sheet multi-purpose tray 1-sheet manual feed slot 100-sheet face down Plain paper, Heavy Paper, Transparency, Label, Index card, Envelope Multi-purpose tray: A4/B5/A5/LGL/LTR/EXE/16K/Custom sizes COM10/Monarch/C5/DL/ISO-B5 width 76.2 ~ 215.9mm x length 187 ~ 355.6mm | Dimensions (W x D x H) Weight Operating environment Control panel | Sound pressure ¹ : Active: 53 dB(A) Standby: Inaudible 379mm x 293mm x 243mm approx. 7 kg Temperature +10 to 30°C Humidity 20% to 80% RH [no condensation] 1 LED indicator 1 Operation key |
| Media weights | Manual feed slot: A4/B5/A5/LGL/LTR/EXE/16K/Custom sizes COM10/Monarch/C5/DL/ISO-B5/Index card width 76.2 ~ 215.9mm x length 127 ~ 355.6mm Multi-purpose tray: 60 to 163 g/m ² Manual feed slot: 60 to 163 g/m ² | CONTROLLER Printer languages Interface and connectivity Operating systems compatibility | Canon Advanced Printing Technology (CAPT) USB 2.0 Hi-Speed Win 7(32/64bit) / Win Vista(32/64bit) / XP(32/64bit) / Server 2008(32/64bit) / Server 2008 R2(64bit) / Server 2003 (32/64bit) / 2000 Mac OS10.4.9 - 10.6.x ² Linux ² |
| CONSUMABLES All-in-One cartridges | | Standard: Cartridge 726 (2,100 pages ³) ⁴ | |
| <p>Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All specifications subject to change without notice</p> <p>Footnotes 1. Declared noise emission in accordance with ISO 9296 2. Web distribution only 3. Based on ISO/IEC 19752 4. Printer ships with 900 pages starter cartridge</p> | | | |

