



See productivity soar with this high performing Color LaserJet MFP. Create A3 colour documents with excellent line and image quality. Enjoy fast print speeds; print, copy, scan, fax<sup>1</sup> and digital sending functionality plus exceptional ease of use.

**Ideal for workgroups (of 6 to 15 users) and departmental environments (up to 20 users) within large and medium enterprise managed office environments who need print, copy, scan, fax and digital sending functionality, up to A3 format as well as high quality colour capabilities to produce a range of internal and external business communications.**

**Boost workgroup productivity with fast print speeds, more functionality and outstanding performance.**

Increase output with speeds of up to 31 ppm<sup>2</sup> and 41 ppm<sup>3</sup> in colour and black (A4), and a first printed page in around 12 seconds. Handle complex jobs fast with an 835 MHz microprocessor and 512 MB memory expandable up to 1 GB. Speed up workflow with scan-to e-mail, scan-to network folder, scan-to printer, and fax<sup>4</sup>. Get peace of mind with security solutions like job authentication, encryption and network protection. Paper handling options include a booklet maker and stapler/stacker.

**Exceptionally easy to use and manage with an intuitive design and touch screen control panel.**

Find applications quickly and experience consistency with the Easy Select<sup>5</sup> control panel's intuitive display. Feature and device management compatibility across your MFP fleet ensures ease of use. Cut costs and save time with HP Web Jetadmin fleet management software: install, configure and manage remotely, automate routine tasks and track supplies usage. Extend your MFP's capabilities: streamline workflows with advanced solutions like integrated capture, job accounting and security.

**Achieve outstanding results with superior colour accuracy and excellent output quality.**

Create high quality colour documents up to A3<sup>6</sup> that make a big impact with HP ImageREt 4800. Get exceptional line acuity with up to 1200x600 dpi operating mode, ideal for detailed plans and architectural drawings. Ensure superior colour accuracy with support for colour matching standards and Pantone certification. Produce reliable, consistent, high gloss, colour print quality with improved HP ColorSphere toner. Advanced paper handling options include a booklet maker and a stapler/stacker.

<sup>1</sup> Optional accessory  
Please purchase separately  
Available as standard with HP Color LaserJet CM6030f and CM6040f MFP

<sup>2</sup> With CM6030 MFP series

<sup>3</sup> With CM6040 MFP series

<sup>4</sup> Optional accessory  
Please purchase separately  
Available as standard with HP Color LaserJet CM6030f and CM6040f MFP

<sup>5</sup> Buyer's Lab gave HP a "Pick of the Year" award in December 2006 for Outstanding Achievement for the User Interface Design of its Multifunction Printers

<sup>6</sup> Up to SRA3.



HP Color LaserJet  
CM6030 MFP



HP Color LaserJet  
CM6030f MFP



HP Color LaserJet  
CM6040 MFP



HP Color LaserJet  
CM6040f MFP

## Series at a glance



### HP Color LaserJet CM6030 MFP

- Print and copy speed up to 31ppm A4 and 17ppm A3
- Effective output quality with ImageREt4800 and up to 1200x600 dpi
- 600x600 dpi scan resolution
- 512MB RAM expandable to 1GB
- 80GB Hard Disk drive capacity
- 835MHz processor
- Automatic two-sided printing
- 50-sheet Automatic Document Feeder (ADF)
- Input capacity of 1100-sheet (from 100-sheet MP tray and 2 x 500-sheet trays)
- Standard 500-sheet output capacity
- Colour Access Controls



### HP Color LaserJet CM6030f MFP

- HP Color LaserJet CM6030 MFP plus:
- Analog fax
- 2 additional 500-sheet trays
- bringing the total input capacity to 2100-sheet.



### HP Color LaserJet CM6040 MFP

- Print and copy speed up to 41ppm A4 and 23ppm A3
- Effective output quality with ImageREt4800 and up to 1200x600 dpi
- 600x600 dpi scan resolution
- 512MB RAM expandable to 1GB
- 80GB Hard Disk drive capacity
- 835MHz processor
- Automatic two-sided printing
- 50-sheet Automatic Document Feeder (ADF)
- Input capacity of 1100-sheet (from 100-sheet MP tray and 2 x 500-sheet trays)
- Standard 500-sheet output capacity
- Colour Access Controls
- Blue Angel certified



### HP Color LaserJet CM6040f MFP

- HP Color LaserJet CM6040 plus:
- Analog fax
- 2 additional 500-sheet trays (bringing the total input capacity to 2100-sheet)
- Energy Star certified

## Recommended accessories



CB458A  
HP Color LaserJet CB458A  
220V Fuser Kit



CB459A  
HP Color LaserJet CB459A  
Roller Kit



CB463A  
HP Color LaserJet CB463A  
Imaging Transfer Kit



CE487A  
HP CM6000 MFP Series  
ADF Roller Kit



CC517A  
HP Color LaserJet CM6000  
Series Stapler/Stacker



CC516A  
HP Color LaserJet CM6000  
Series Booklet Maker



C8091A  
HP Staple Cartridge



Q3701A  
HP LaserJet MFP Analog Fax  
Accessory 300



CC383A  
HP Staple Cartridge Booklet  
Maker (2 x 2000 staples)



T1936AA  
HP Digital Sending Software  
4



Q7559A  
HP 512 MB 167 MHz  
200-pin DDR DIMM  
Memory Module



J8007G  
HP Jetdirect 690n Wireless  
802.11g Internal Print Server

## Operating and warranty specifications

<b>Operating environment</b>	Operating temperature: 15 to 27° C . Recommended operating temperature: 15 to 27° C . Operating humidity: 10 to 80% RH. Operating humidity recommended: 30 to 70% RH . Storage temperature: 0 to 35° C . Storage humidity: 35 to 85% RH. Noise level per ISO 9296: sound power: LwAd 6.8 B(A) (active/printing), 7.3 B(A) (active/copy or scan), 4.3 B(A) (ready). Sound pressure: LpAm 56.8 dB(A) (active/printing), 57.1 B(A) (active/copy or scan), 40.3 dB(A) (ready)
<b>Certifications</b>	CISPR 22: 2005/EN 55022: 2006 Class B, EN 61000-3-2: 2000 +A2, EN 61000-3-3: 1995+A1, EN 55024: 1998+A1 +A2, FCC Title 47 CFR, Part 15 Class B (USA), ICES-003, Issue 4, (Canada), GB9254-1998, EMC Directive 2004/108/EC with CE Marking (Europe), other EMC approvals as required by individual countries . Regulatory standards: IEC 60950-1 (International), EN 60950-1 +A11 (EU), IEC 60825-1+A1+A2, UL/cUL Listed (US/Canada), GS license (Europe), EN 60825-1+A1+A2 Class 1, 21 CFR Ch. 1/SubCh. J and Laser Notice#50 (July 26th 2001)(Class 1 Laser/LED Device) GB4943-2001, Low Voltage Directive 2006/95/EC with CE Marking (Europe). Other safety approvals as required by individual countries . ENERGY STAR: Yes
<b>Warranty</b>	1 year Next Business Day On-Site standard. Warranty and support options vary by product, country and local legal requirements.

## Ordering information



**HP Color LaserJet CM6030 MFP (CE664A)**  
HP Color LaserJet CM6030 MFP unit, CD Assembly (Driver/User Guide), Digital Sending Software (DSS) Trial Version CD, Getting Started Guide, Wall Poster with Helpful Tips, Telephone Support Flyer, Power Cords, Control Panel Overlays, and the Cyan, Magenta, Yellow and Black Toner Cartridges already installed within the device.



**HP Color LaserJet CM6030f MFP (CE665A)**  
Same as the CM6030, except: HP Color LaserJet CM6030f MFP unit, and fax cable



**HP Color LaserJet CM6040 MFP (Q3938A)**  
Same as the CM6030, except: HP Color LaserJet CM6040 MFP unit



**HP Color LaserJet CM6040f MFP (Q3939A)**  
Same as the CM6030, except: HP Color LaserJet CM6040f MFP unit, and fax cable

## Accessories, Supplies and Support

### Accessories

<b>CB458A</b>	HP Color LaserJet CB458A 220V Fuser Kit
<b>CB459A</b>	HP Color LaserJet CB459A Roller Kit
<b>CB463A</b>	HP Color LaserJet CB463A Imaging Transfer Kit
<b>CE487A</b>	HP CM6000 MFP Series ADF Roller Kit
<b>CC517A</b>	HP Color LaserJet CM6000 Series Stapler/Stacker
<b>CC516A</b>	HP Color LaserJet CM6000 Series Booklet Maker
<b>C8091A</b>	HP Staple Cartridge
<b>Q3701A</b>	HP LaserJet MFP Analog Fax Accessory 300
<b>CC383A</b>	HP Staple Cartridge Booklet Maker (2 x 2000 staples)
<b>T1936AA</b>	HP Digital Sending Software 4
<b>Q7559A</b>	HP 512 MB 167 MHz 200-pin DDR DIMM Memory Module

### Supplies

<b>CB390A</b>	HP Color LaserJet CB390A Black Print Cartridge with ColorSphere Toner Average continuous Black Cartridge yield 19,500 standard pages. Declared yield value in accordance with ISO/IEC 19798*
<b>CB381A</b>	HP Color LaserJet CB381A Cyan Print Cartridge with ColorSphere Toner Average continuous composite Cyan/Yellow/Magenta Cartridge yield 21,000 standard pages. Declared yield value in accordance with ISO/IEC 19798*
<b>CB382A</b>	HP Color LaserJet CB382A Yellow Print Cartridge with ColorSphere Toner

<b>CB383A</b>	HP Color LaserJet CB383A Magenta Print Cartridge with ColorSphere Toner Average continuous composite Cyan/Yellow/Magenta Cartridge yield 21,000 standard pages. Declared yield value in accordance with ISO/IEC 19798*
<b>CB384A</b>	HP Color LaserJet CB384A Black Imaging Drum 35,000 pages*
<b>CB385A</b>	HP Color LaserJet CB385A Cyan Imaging Drum 35,000 pages*
<b>CB386A</b>	HP Color LaserJet CB386A Yellow Imaging Drum 35,000 pages*
<b>CB387A</b>	HP Color LaserJet CB387A Magenta Imaging Drum 35,000 pages*

### Connectivity

<b>J8007G</b>	HP Jeldirect 690n Wireless 802.11g Internal Print Server
---------------	--

### Service & support

<b>UJ165A/E</b>	HP Care Pack, Next Business Day On site Response, 3 years
<b>UJ169E</b>	HP Care Pack, Same Business Day On site Response, 4-Hour, 13x5, 3 years
<b>UJ166E</b>	HP Care Pack, Next Business Day On site Response, 4 years
<b>UJ167E</b>	HP Care Pack, Next Business Day On site Response, 5 years
<b>UJ174PE</b>	HP Care Pack, Post Warranty, Next Business Day On site Response, 1 year
<b>UJ176PE</b>	HP Care Pack, Post Warranty Same Business Day On site Response, 4-Hour, 13x5, 1 year

For a complete list of supplies, accessories and services, please refer to <http://www.hp.com>  
For workflow, device management and other solutions, please visit the Global Solutions catalog: [www.hp.com/go/gsc](http://www.hp.com/go/gsc)

\* Declared yield value in accordance with ISO/IEC 19798



## Technical specifications

<b>Print technology</b>	Laser			
<b>Print speed</b>	A4: CM6030: Up to 31 ppm; CM6030f: Up to 31 ppm; CM6040: Up to 41 ppm; CM6040f: Up to 41 ppm. A3: CM6030: Up to 17 ppm; CM6030f: Up to 17 ppm; CM6040: Up to 23.5 ppm; CM6040f: Up to 23.5 ppm. First page out black: CM6030: < 15.5 sec (from ready); CM6030f: < 15.5 sec (from ready); CM6040: < 11.5 sec (from ready); CM6040f: < 11.5 sec (from ready) Colour: CM6030: < 15.8 sec (from ready); CM6030f: < 15.8 sec (from ready); CM6040: < 11.5 sec (from ready); CM6040f: < 11.5 sec (from ready); . Warm-up time: less than CM6030: 124.3 sec; CM6030f: 124.3 sec; CM6040: 112 sec; CM6040f: 112 sec Exact speed varies depending on the system configuration, software program and document complexity.			
<b>Processor</b>	835 MHz. PMC-Sierra RM7965 64-bit Microprocessor			
<b>Memory</b>	512 MB. Expandable to 1GB via one DDR SODIMM slot: 128 MB (Q7557A), 256 MB (Q7558A), 512 MB (Q7559A), all memories being 167 MHz 200-pin DDR DIMM. Hard Disk Capacity: Standard, 80 GB			
<b>Print</b>	Quality	HP ImageREt 4800		
	Resolution	Up to 1200 x 600 dpi		
	Printer languages	HP PCL 5, HP PCL 6, HP Postscript level 2 emulation (default), HP Postscript level 3 emulation is supported		
	Economical printing	Two-sided printing and N-up printing/copying (saves paper), Colour Access Control (printing/copying in black saves toner)		
	Typefaces/fonts	Set of 80 HP fonts (plus Greek, Hebrew, Cyrillic, Arabic)		
	Recommended monthly page volume	CM6030: 5000 to 10000; CM6030f: 5000 to 10000; CM6040: 8000 to 15000; CM6040f: 8000 to 15000		
	Print margins (mm)	Top: 4.2 mm. Left: 4.2 mm. Right: 4.2 mm. Bottom: 4.2 mm		
	Maximum print area	316 x 453.2 mm		
<b>Fax</b>	Modem speed	13 sec per page		
	Telecom compliance	CM6030f: ES 203 021, R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe), FCC Part 68, Industry Canada CS03, NOM-151-SCTI-1999 (Mexico), PTC-200 (New Zealand), AS/ACIF S002: 2001 (Australia), IDA PSTN1 (Singapore), TPS002-01 (Malaysia), IG 0005-11 (Taiwan), HKTA 2011 (Hong Kong SAR), YD514, YD/T589, YD703, GB3382 (China) other Telecom approvals as required by individual countries; CM6040f: ES 203 021, R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe), FCC Part 68, Industry Canada CS03, NOM-151-SCTI-1999 (Mexico), PTC-200 (New Zealand), AS/ACIF S002: 2001 (Australia), IDA PSTN1 (Singapore), TPS002-01 (Malaysia), IG 0005-11 (Taiwan), HKTA 2011 (Hong Kong SAR), YD514, YD/T589, YD703, GB3382 (China), other Telecom approvals as required by individual countries		
	Modem	33.6 Kbps v 34 Fax		
	Fax resolution	Standard: 100 x 100 dpi. Superfine: 300 x 300 dpi		
<b>Digital sending</b>	File formats	PDF, JPEG, TIFF, or MTIFF. (OCR supports PDF, TEXT, RTF (Microsoft® Word® Compatible), XML, HTML; send to workflow (DSS) supported file types include XML, searchable PDF, TXT, RTF (Microsoft® Word® Compatible), HTML, PDF, JPEG, TIFF, and MTIFF		
	Installation	Fast Ethernet, Gigabit Ethernet, 802.11b wireless		
	Features	Standard: Scan to folder (includes shared address book for fax), scan direct to e-mail server, send to e-mail, analog fax, LDAP e-mail addressing; authentication: Windows® negotiated (Kerberos and NTLM), group 1 and group 2 PIN, LDAP, authentication manager. Optional: Advanced digital sending capabilities via optional HP Digital Sending Software		
<b>Scan</b>	Type	Flatbed, ADF. Colour scanning: Yes		
	Scan resolution	Optical: Up to 600 dpi		
	Grey scale levels	256		
	Scannable area	Minimum media size: 12,7 x 12,7 cm. Maximum media size: 29,7 x 43,2 cm		
	Margins for scanned items	Left: 4.2. Top: 4.2. Right: 4.2. Bottom: 4.2		
<b>Copy</b>	Copy speed	CM6030: Up to 31 cpm; CM6030f: Up to 31 cpm; CM6040: Up to 41 cpm; CM6040f: Up to 41 cpm		
	Copy resolution	Up to 600 x 600 dpi		
	Multiple copies	Up to 999		
	Reduce/enlarge	25 to 200%		
<b>Media handling</b>	<b>Input:</b>	<b>Capacity</b>	<b>Weight</b>	<b>Size</b>
	Tray 1	sheets 100, envelopes 10	60 to 220 g/m <sup>2</sup>	A3, A4, A4-R, A5, A6, RA3, SRA3, B4 (JIS), B5 (JIS), B6 (JIS), 8K, 16K, D postcard, envelopes (#9, #10, Monarch, B5, C5, C6, DL); 99 x 140 mm to 320 x 457 mm
	Tray 2	sheets: 500	60 to 220 g/m <sup>2</sup>	A3, A4, A4-R, A5, B4 (JIS), B5 (JIS), 8K, 16K; 148 x 210 mm to 297 x 432 mm
	Tray 3	sheets: 500 (same for Tray 4 and Tray 5)	60 to 220 g/m <sup>2</sup> (same for Tray 4 and Tray 5)	A3, A4, A4-R, A5, RA3, SRA3, B4 (JIS), B5 (JIS), 8K, 16K; 148 x 210 mm to 320 x 457 mm (same for Tray 4 and Tray 5)
	ADF	sheets: 50	60 to 220 g/m <sup>2</sup>	A3, A4, B4, B6
	<b>Output:</b>	Sheets: Up to 500-sheet without finisher		
	Duplex printing: Automatic (standard)			
<b>Media types</b>	Paper (bond, recycled, glossy, mid-weight, heavy, heavy glossy, extra heavy, extra heavy glossy, tough, rough), transparencies, labels, envelopes, cardstock			
<b>Interface and connectivity</b>	Hi-Speed USB (compatible with USB 2.0 specifications) device port, one open EIO slot, HP Jetdirect Gigabit Ethernet embedded print server, fax port, Foreign Interface Harness (FIH) port, PCI express. Optional: HP Jetdirect EIO internal print servers, HP Jetdirect external print servers, wireless print server, printer adapter			
<b>Operating systems compatibility</b>	Microsoft® Windows® 2000, XP, Server 2003; Windows Vista®; Mac OS X v10.2.8, v10.3, v10.4 and higher			
<b>Network operating systems compatibility</b>	Microsoft® Windows® 2000, Server 2003, XP, 2003 64-bit, XP 64-bit; Windows Vista®, 64-bit (For Microsoft® IPv6 compatible with Microsoft® Windows® 2003, XP, and Windows Vista®); Novell® 5.1 or higher; Mac OS X v10.2, v10.3, v10.4 or higher; RED HAT Linux 7.x or higher; SUSE Linux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris® 2.5 or higher (SPARC® systems only); IBM® AIX 3.2.5 or higher; MPE-iX; Citrix® MetaFrame Server; Windows® Terminal Services			
<b>Minimum system requirements</b>	Microsoft® Windows® 2000: 333 MHz processor with 64 MB RAM; Microsoft® Windows® XP: 333 MHz processor with 128 MB RAM; Microsoft® Windows® Server 2003: 550 MHz processor with 128 MB RAM; Windows Vista®: 800 MHz processor with 512 MB RAM; CD-ROM/DVD drive. Internet connection, USB or network port connection. Mac OS X v10.2.8, v10.3, v10.4 and higher with 128 MB RAM, CD-ROM, 160 MB of free hard disk space (For Mac OS v10.4 and higher, PowerPC and Intel® Core Processor Macs are supported)			
<b>Standard software</b>	Print drivers and installation software on CD-ROM: HP common installer, HP Internet installer, HP common drivers, HP Installation Wizard, Postscript Printer Description (PPD) files, Printer Dialog Extensions (PDEs), HP Printer Utility for use with Macintosh computers			
<b>Control panel</b>	5 LED indicator lights, 10-key numeric pad, graphical touch screen display (192 x 72 mm) 640 x 240 resolution with adjustable contrast			
<b>Power</b>	Requirements: Input voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), 10.5 amp; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), 5.5 amp. *115 VAC unit tested. Data from colour simplex printing and copying.			
<b>Dimensions (w x d x h)</b>	Out of package: 704 x 673 x 988 mm. Packaged: 935 x 800 x 1210 mm			
<b>Weight</b>	Out of package: CM6030: 139.87 kg; CM6030f: 144.91 kg; CM6040: 139.87 kg; CM6040f: 144.91 kg. Packaged: CM6030: 154.92 kg; CM6030f: 159.96 kg; CM6040: 154.92 kg; CM6040f: 159.96 kg			
<b>Printer management</b>	HP Toolbox, HP Web Jetadmin, HP Embedded Web Server			

<http://www.hp.com/uk>



© Copyright 2008 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 04/08 4AA1-3943EEE

